

Bale Movers, page 1



RBM2

Built to handle up to 3000 lbs. Two point hitch, Length 58", Width 38", Category II hitch. Pins standard.



RBM3

Built to handle up to 3000 lbs. Three Point hitch. The top hitch bracket is slotted allowing the forks to float out and under materials being picked up.



RBM1

Economical bale mover for large Bales. Category II hitch. 43", 2" diameter solid steel shaft 48" long. Reinforced with 3/8" thick gusset.



RBM1S

Economical bale mover for large bales with safety spikes to increase bale stability. Category II hitch. 2" diameter solid steel shaft. 48" long. Reinforced with 3/8" thick gusset.

Bale Movers, page 2



RBM1B

Economical bale mover for large round bales. Attaches to front end loader bucket. Binder included. 2" diameter solid steel shaft 48" long. Reinforced with 3/8" thick gusset.



SM6

Heavy duty mover for jumbo bales and mini stacks. Also useful as a utility carrier around the farm. The 3 tines allow for easy movement under and out of a bale or stack. The top hitch bracket is slotted allowing the forks to float out and under materials being picked up.

Capacity: 4000 lbs. Length: 6' 3"

Width: 6'

SM8 - Same as SM6, except 4 tines, 8' wide, 6'3" long



Pallet Forks

Built to handle 3000 lbs. Attach directly to front end bucket. Forks 48" long.

Not recommended for round bales.

Specifications are subject to change without notice.